

VARIATION NOTICE

Pollution Prevention and Control Act 1999

The Environmental Permitting (England and Wales) Regulations 2010

Regulation 20

certified a true copy of a notice
served by me. Addressed as

this copy

IPSWICH
BOROUGH COUNCIL

by Recorded Del. Date 26.07.11

Name V. Addy Signature

PPC Permit Ref: 7/VPA/8/09
Variation notice Ref: WK201104345
EP Permit Ref: DC2/VPA/7/11

To:

Fircroft Laundry, 153 Fircroft Road, Ipswich, Suffolk, IP1 6PT

Ipswich Borough Council ("the Council"), in the exercise of the powers conferred upon it by regulation 20 of the Environmental Permitting (England and Wales) Regulations 2010 hereby gives you notice as follows:

The Council has decided to vary the conditions of permit reference 7/VPA/8/09 granted under regulation 10 of the Pollution Prevention and Control (England and Wales) Regulations 2000 in respect of the operation of the installation at Fircroft Laundry, 153 Fircroft Road, Ipswich, Suffolk, IP1 6PT.

The varied consolidated permit reference DC2/VPA/7/11 and the date on which it takes effect are specified in Schedule 1 to this notice.

Signed on behalf of Ipswich Borough Council

.....
Varuna Addy
(Acting) Principal Environmental Health Officer
An authorised Officer of the Council

Date: 25.07.11

Permit issued by:


Environmental Protection Services
Ipswich Borough Council
Floor 3 West
Grafton House
15-17 Russell Road
Ipswich
IP1 2DE

Telephone: 01473 433115
Fax: 01473 433062
Website: www.ipswich.gov.uk
Email: environmentalprotection@ipswich.gov.uk

Schedule 1

The conditions contained in the varied consolidated permit DC2/VPA/7/11 overleaf come into effect immediately and supersede any previous permits.

Signed on behalf of Ipswich Borough Council


.....
Varuna Addy
(Acting) Principal Environmental Health Officer
An authorised Officer of the Council

Date: 25.07.11

Permit With Introductory Note

The Pollution Prevention and Control Act 1999
The Environmental Permitting (England and Wales) Regulations 2010



**Fircroft Laundry and
Dry Cleaners**
153 Fircroft Road
Ipswich
IP1 6PT

LAPPC Permit Ref
No: DC2/VPA/7/11

Contents	Page
Introductory Note	2
Permit	5
Installation Details	6
Permit Conditions	7
Appendices	10

Chronicle	Date	Comments
LAPPC Application Duly made	24 th October 2006	7/SR/1/06
Consultation Permit	3 rd August 2007	7/LK/8/07
Permit Issued	18 th September 2007	7/LK/8/07
Permit Variation Issued	11 th August 2009	7/VPA/8/09
Permit	26 th July 2011	DC2/VPA/7/11

Permit issued by:

Environmental Protection Services
Ipswich Borough Council
Floor 3 West
Grafton House
15-17 Russell Road
Ipswich
IP1 2DE

Telephone: 01473 433115
Fax: 01473 433062
Website: www.ipswich.gov.uk
Email: environmentalprotection@ipswich.gov.uk

INTRODUCTORY NOTE

This introductory note does not form part of the permit

The following Permit is issued under Regulation 13 of the Environmental Permitting (England and Wales) Regulations 2010, to operate a scheduled installation carrying out an activity, or activities covered by the description in section 7 in Part 2 to Schedule 1 of the EP regulations, to the extent authorised by the Permit.

Conditions within this Permit detail Best Available Techniques (BAT), for the management and operation of the installation, to prevent, or where that is not practicable, to reduce emissions.

In determining BAT, the Operator should pay particular attention to relevant sections of the Secretary of State's Process Guidance Note 6/46(11), and any other relevant guidance. Techniques include both the technology used and the way in which the installation is designed, built, maintained, operated and decommissioned.

Note that the Permit requires the submission of certain information to the Regulator, and in addition, the Regulator has the power to seek further information at any time under Regulation 60 of the EP Regulations provided that the request is reasonable.

Public Registers

Information relating to Permits, including the application, is available on public registers in accordance with the EP Regulations. Certain information may be withheld from the public registers where it is commercially confidential, or if it is in the interest of national security to do so.

Variations to the Permit

The Regulator may vary the permit in the future, by serving a variation notice on the Operator. Should the Operator want any of the conditions of the Permit to be changed, a formal application must be submitted to the Regulator (the relevant forms are available from the Regulator). The Status Log that forms part of this introductory note will include summary details of this Permit, variations issued up to that point in time and state whether a consolidated version of the Permit has been issued.

Transfer of the Permit or Part of the Permit

Before the Permit can be wholly or partially transferred to another Operator, an application to transfer the Permit has to be made jointly by the existing and proposed Operators. A transfer will not be approved if the Regulator is not satisfied that the proposed Permit holder will be the person having control over the operation of the installation, or will not comply with the conditions of the transferred Permit. In addition, if the Permit authorises the Operator to carry out a specified waste management activity, the transfer will not be approved if the Regulator does not consider the proposed Permit holder to be a 'fit and proper person' as required by the EP Regulations.

Surrender of the Permit

Where an operator intends to cease the operation of an installation (in whole or in part) the Regulator should be informed in writing. Such notification must include the information specified in Regulation 24(3) of the EP Regulations.

Responsibility under Workplace Health and Safety Legislation

The permit is given in relation to the requirements of the EP Regulations. It must not be taken to replace any responsibilities an Operator may have under the workplace health and safety legislation.

Appeal Against Permit Conditions

Any person who is aggrieved by the conditions attached to a Permit can appeal to the Secretary of State for Environment, Food & Rural Affairs. Appeals must be received by the Secretary of State no later than 6 months from the date of the decision (the date of the Permit).

Appeals relating to installations in England should be received by the Secretary of State for Environment, Food & Rural Affairs. The address is as follows:

**The Planning Inspectorate
Environmental Appeals Administration
Room 4/19 – Eagle Wing
Temple Quay House
2 The Square
Temple Quay
Bristol, BS1 PN**

The appeal must be in the form of a written notice or letter stating that the person wishes to appeal and listing the condition(s) which is/are being appealed against. The following five items must be included:

- 1) A statement of the grounds of appeal;
- 2) A copy of any relevant application;
- 3) A copy of any relevant Permit;
- 4) A copy of any relevant correspondence between the person making the appeal and the Council;
- 5) A statement indicating whether the appellant wishes the appeal to be dealt with
 - by a hearing attended by both parties and conducted by an inspector appointed by the Secretary of State; or
 - by both parties sending the Secretary of State written statements of their case (and having the opportunity to comment upon one another's statements).

At the same time, the notice of appeal and documents (a) and (e) must be sent to the Council, and the person making the appeal should inform the appropriate Secretary of State that this had been done.

- An appeal will not suspend the effect of the conditions appealed against; the conditions must still be complied with.
- In determining an appeal against one or more conditions, the Act allows the Secretary of State in addition to quash any of the other conditions not subject to the appeal and to direct the local authority to either vary any of these conditions or to add new conditions.

Copyright of any maps if provided with this Permit

Any Ordnance Survey mapping included if within this publication is provided by Ipswich Borough Council, under licence from the Ordnance Survey in order to fulfil its public function to provide information regarding environmental searches, site notices or authorisations for prescribed processes. Persons viewing this mapping should contact Ordnance Survey copyright for advice where they wish to licence Ordnance Survey mapping for their own use.

Talking to us

Please quote the Permit Number if you contact the Regulator about this permit. To give a notification, the Operator should telephone 01473 433115 or any other number notified in writing by the Regulator for that purpose.

~ End of Introductory Note~

Permit With Introductory Note

The Pollution Prevention and Control Act 1999
The Environmental Permitting (England and Wales) Regulations 2010



LAPPC Permit Ref No: DC2/VPA/7/11

Ipswich Borough Council (hereinafter known as the Regulator) in exercise of its powers under Regulation 13 of The Environmental Permitting (England and Wales) Regulations 2010, hereby authorises:

Steven and Belinda Driver Trading as Fircroft Laundry and Dry Cleaners (hereinafter known as the Operator)

whose Registered Office is at:

**153 Fircroft Road
Ipswich
IP1 6PT**

to operate an installation at:

**153 Fircroft Road
Ipswich
IP1 6PT**

to the extent authorised by and subject to the conditions of this Permit.

Signature:

Varuna Addy
(Acting) Principal Environmental Health Officer
The Authorised Officer for this purpose

Date: 25.07.11

Permit issued by:

Environmental Protection Services
Ipswich Borough Council
Floor 3 West
Grafton House
15-17 Russell Road
Ipswich
IP1 2DE

Telephone: 01473 433115
Fax: 01473 433062
Website: www.ipswich.gov.uk
Email: environmentalprotection@ipswich.gov.uk

INSTALLATION DETAILS

Fircroft Laundry and Dry Cleaners, 153 Fircroft Road, Ipswich, IP1 6PT.

The above named company is permitted to operate a dry cleaning installation using the dry cleaning machine described below subject to compliance with the conditions detailed in this permit and within the site boundary shown on the Site Plan in Appendix 1:

Make	Model	Serial Number	Load Capacity	Date of Installation	Dry Cleaning Solvent
BÖWE	P300	264/9502	15 Kg	Dec 1994	Perchloroethylene

PERMIT CONDITIONS

1. Operations must be carried out in such a manner that no more than 20 grams of solvent per kilogram of product cleaned and dried shall be emitted as measured and reported annually. The 20 grams includes all organic solvents used within the installation e.g. dry cleaning solvent, water-proofing solutions and spot cleaning solutions.
2. A weekly inventory of solvent usage, product cleaned and solvent waste sent for recovery or disposal shall be maintained and held on site for inspection by the regulator for at least 12 months. Further, the operator shall retain records of solvent purchased for at least 12 months.

Note: The revised solvent management balance sheet for dry cleaning installations (found on the DEFRA website: www.defra.gov.uk) can be used to demonstrate compliance with conditions 1 and 2 above.

3. A copy of the following shall be sent to the Council at the frequency given below:

Information to be sent to the Council	Frequency at which this information should be sent
The monthly inventory sheets for the previous quarter.	Once a quarter
The record of regular maintenance during the previous 12 months, referred to in Condition 4.	Once a year
A list of staff nominated and trained in accordance with Conditions 6 and 7.	Once a year

4. The operator shall implement the schedule of procedures, checks and maintenance requirements to each dry cleaning machine as listed in Appendix 2.
5. The operator shall notify the regulator in writing 14 days prior to any proposed significant alteration to the operation, or modification of the installation which may have an effect on emissions of volatile organic compounds from the installation, in particular changes to the matters in condition 4.

6. All operating staff must know where the operating manual for each dry cleaning machine can be found and have ready access to it.
7. All operating staff must have been trained in the operation of each dry cleaning machine and the control and use of dry cleaning solvents. The training received must be recorded.
8. The machine shall be installed and operated in accordance with supplier recommendations, so as to minimise the release of volatile organic compounds to air, land and water.
9. In the case of abnormal emissions, malfunction or breakdown leading to abnormal emissions the operator must:
 - investigate immediately and undertake corrective action; adjust the process or activity to minimise those emissions; and
 - adjust the process or activity to minimise those emissions; and
 - promptly record the events and actions taken
 - in this condition abnormal emission will include any detectable solvent smell other than in the area of the dry cleaning machine
10. In cases of non-compliance causing immediate danger to human health, operation of the activity must be suspended; and the regulator informed within 24 hours.
11. Dry cleaning machines shall be operated as full as the type of materials to be cleaned will allow (eg full loads for light non delicate materials such as suits. Delicates and heavy materials, such as wedding dresses and blankets may need to be cleaned in part loads).
12. Where cleaning solvents containing VOCs are not received in bulk they shall be stored:
 - in the containers they were supplied in with the lid securely fastened at all times other than when in use; and
 - within spillage collectors, of suitable size and made of impervious and corrosion-proof materials and
 - away from sources of heat and bright light; and
 - with access restricted to only appropriately trained staff.
 - The lids of the containers shall only be removed when the container is next to the cleaning machine ready for filling. Cleaning solvents shall be obtained in containers of a size which allows the entire container to be emptied into the machine at each topping up. Once emptied, the lid of the container shall be replaced securely.

(Note: from a health and safety point of view a well ventilated area should be used.)
13. Spot cleaning with organic solvents or organic solvent borne preparations shall not be carried unless they are the only method of treating a particular stain on a material to be cleaned.
14. The dry cleaning machine loading door shall be kept closed when not in use.

(Note: Where an extract fan is fitted to maintain a negative pressure within the machine during unloading, the exhaust from this fan should be directed to a carbon adsorption filter prior to discharge to atmosphere).


15. The dry cleaning machine loading door shall be closed before the start-up of the machine, and kept closed at all times through the drying and cleaning cycle.
 - All machines installed after 19 May 2005 shall have interlocks to prevent start-up of the machine until the loading door is closed and to prevent opening of the loading door until the machine cycle has finished and the cage has stopped rotating.
 - All machines installed after 19 May 2005 shall have interlocks to automatically shut down the machine under any of the following conditions: cooling water shortage, failure of the cooling ability of the still condenser, failure of the cooling ability of the refrigeration system or failure in the machine heating system resulting in the inability to dry the load.
16. The still, button trap and lint filter doors shall be closed before the start-up of the machine and kept closed at all times through the drying and cleaning cycle.
17. All machines installed after 19 May 2005 shall have interlocks to automatically shut down the machine if the still, button trap and lint filter doors are not properly closed.
18. The still shall have a thermostatic control device or equivalent, with which to set a maximum temperature, in accordance with manufacturers' recommendations for the solvent used.
19. All new and substantially refurbished machines shall have a spillage tray with a volume greater than 110% of the volume of the largest tank within the machine.
(Note: This does not remove the need to comply to health and safety recommendations relating to the fitting of spill trays to existing machines)
20. All machines installed after 19 May 2005 shall have a secondary water separator to minimise potential solvent losses. Where this is not an integral part of the machine then the operator shall select and install a method that will achieve an equivalent degree of separation.
21. Prior to disposal, containers contaminated with solvent shall be stored with the lids securely fastened to minimise emissions from residues during storage prior to disposal, and labelled so that all that handle them are aware of their contents.
(Note: Empty containers should where possible, be returned to the supplier.)
22. Solvent contaminated waste, for example still residues, shall be stored:
 - in suitable sealed containers with the lid securely fastened at all times other than when in use; and
 - on a suitable impervious floor (such as a concrete floor, if necessary coated with flooring paint); and
 - away from any drains which may become contaminated with residues as a result of spillage
 - away from sources of heat and bright light; and
 - with access restricted to only appropriately trained staff.

(Note: from a health and safety point of view a well-ventilated area should be used.

23. Equipment to clean up spillages must be quickly accessible in all solvent handling and storage areas.
24. The operator shall maintain records incorporating details of all maintenance, testing, repair work carried out on each dry cleaning machine and the scales used to weigh the loads, along with details of training required under condition 6. The records shall be available within 7 days upon request by the regulator.
25. Spares and consumables in particular, those subject to continual wear shall be held on site, or should be available at short notice from guaranteed suppliers, so that plant breakdowns can be rectified rapidly.
26. Where a continuous PER monitoring device has been fitted for health and safety reasons, it shall be maintained and calibrated in accordance with the manufacturers recommendations. As a high reading on the monitor indicates leaks and other malfunctions which have lead to the release of PER, then this will also indicate potential non compliance with the environmental requirements of this permit.

(Note: An alternative is to use a hand-held device to detect leaks as this can be used in close proximity to the machine to detect minor leaks that would not be detected by a remote monitor).

Appendix 1



Appendix 2

Maintenance

Daily:

- Clean button trap
- Clean lint filter
- Check safety tray for solvent

Weekly:

- Empty water separator into still
- Empty condenser
- Maintenance program P36 with emission free still rake out

Monthly:

- Clean strainer