



Received by UPA 24.03.09

Ipswich Borough Council Environmental Protection Services Civic Centre Civic Drive Ipswich IP1 2EE

17th February 2009

Shell U.K. Oil Products Limited
Retail
PO Box 403
Staines
TW18 3ZB
United Kingdom
Tel +44 (0) 1784 897 852
Fax +44 1784 897 845
Internet http://www.shell.com/uk

Vapour Recovery Stage II Application

Dear Sir/Madam

Please find enclosed the completed application form regarding Vapour Recovery Stage || for Site:

- A .i

1) Shell Whitehouse

Could you please send all correspondence and invoice for payment to the following address:

Kerry Toms Shell U.K Oil Products Ltd P.O. Box 403 Staines TW18 3ZB Mrs Von Etzdo-t

Full responsibility for forwarding the Vapour Recovery Permit Oto the sites will be undertaken by the administrator of Shell U.K Limited.

Yours faithfully

Kerry Toms

Retailer Contracting Assistant

Registered in England: No. 3625633 Registered office: Shell Centre, London SE1 7NA VAT Reg. No. GB 235 763 255

Shell U.K.Oil Products Limited is a separate limited company which manages the oil products business of Shell U.K.Limited

LA-IPPC applic	ation form: to be comp	oleted by the operator
For Local Authority use		
Application reference	Officer reference	Date received
	13 2 (4) 1 = 1 =	. 1

A1 Applican	details:	: Shell	UK Limited
-------------	----------	---------	-------------------

A1.1 Name of the installation

SHELL WHITEHOUSE

A1.2 Please give the address of the site of the installation

665 -667 NORWICH ROAD, IPSWICH SUFFOLK

Postcode

IP1 6JZ

Telephone

" (18) com

01473 238950

If known, the Ordnance Survey national grid reference 8 characters, for example, SJ 123 456 (can be obtained from typing postcode into one of the on-line mapping sites)

	Т	М	1	4	1	4	7	1
į				I .			l .	ı

A1.3 Existing permits:

Please give details of any existing LAPPC or LA-IPPC authorisation for the installation, or any waste management licences or water discharge consents, including reference number(s) and type(s):

Vapour Recovery Perr	nit Stage 1 Pe	ermit numb	er LAPPC P	ERMIT RE	G NO 1.2	/RJD/13
	· · ·	·-				
	-	· · · · · · · · · · · · · · · · · · ·				_

Please provide the information requested below about the "Operator" - which means the person who it is proposed will have control over the installation in accordance with the permit (if granted).

A2.1 The operator – please provide the full name of company, partnership, or corporate body
Shell UK Limited

Trading/business name (if different)	
Registered Office address Shell Centre	
York Road	
London	Postcode:SE1 7NA
Principal Office address (if different) Rourke House	
	· · · · · · · · · · · · · · · · · · ·
PO Box 403 Staines Middlesex	Postcode:TW18 3BA
Company registration number 0140141	
A2.2 Holding companies Is the operator a subsidiary of a holding conthe Companies Act 2006? No	mpany within the meaning of section 1159 of
Yes X if 'yes', state name of Shell Transport and Trading Company PLC	of ultimate holding company
Registered office address	
Shell Centre	
York Road	· · · · · · · · · · · · · · · · · · ·
London	
	Postcode SE1 7NA
Principal Office address (if different)	

Postcode
Company registration number: 00054485
A3.1 Who can we contact about your application?
It will help is to have someone who we can contact directly with any questions about y application. The person you name should have the authority to act on behalf of the operator (this can be an agent or consultant).
Name_Kerry Toms
PositionRetailer Contracting Assistant
Address Rourke House
PO Box 403
Staines Middlesex PostcodeTW18 3ZB
telephone number0845 309 3091
fax number 01784897845
email address <u>kerry.toms@shell.com</u>
B1.2 Why is the application being made?
The installation is new
The installation is existing, but changes to the installation or to the EP Regulations means that an LA-IPPC A2 permit is required.
B2.1 Is the service station located under permanent living quarters or working ar See section 2 of PG1/14 (06)
NO YES

B2.2 When was equipment for vapour collection during the filling of underground storage tanks installed or when will it be installed?

Not Known

B2.3 When was **equipment for vapour** recovery during filling of vehicle fuel tanks installed or when will it be installed (only for installations that are required to have a "stage II" vapour recovery system in place.

23RD JULY 2008

B2.4 Volume of petrol unloaded into the service station in each of the last three calendar years (see section 2 of PG1/14 (06) for the relevant timescales) in cubic metres (i.e. litres divided by 1000) Circle the appropriate band

Year		VOL	JME OF PETRO	L/m3	
2005	<100	100-500	501-1000	>1000	/ >3500
2006	<100	100-500	501-1000	>1000	>3500
2007	<100	100-500	501-1000	>1000	\ > 3500 /

B2.5	Are deliveries Driver "Controlled"	/ "Driver Unassisted"
NO	YES	

B2.6 At a maximum how many tanker compartments discharge into storage tanks at any one time or will do so once a vapour collection system is in place. If the latter information is not known a statement of what assessment will be made to determine this information and within what timescale. The information supplied under item 11 should be supplemented by a site specific assessment (See section 6 of PG1/14(06)

1000 . . .

TWO

B2.7 Are diesel storage tanks connected to the vapour balance system?

(NO)	YES

B2.8 Measures taken or to be taken for vapour emission control, both during unloading and storage

_	e 1 vapour reco	•

B2.9 Please attach process diagrams and plans of vapour collection equipment (including height and location of vent pipes). This should include equipment for recovery of

vapours during filling of underground storage tanks and for instillations that are required to have a "stage II" vapour recovery system in place, for filling of petrol tanks.

B2.10	Unloading procedure and instructions (Please attach)	
B2.11 be spe	Details of supervision, Training and Qualifications of Operating staff (Decific to onsite staff and include general statements concerning delivery d	tails should rivers)
vapour have a	Schedule of maintenance of vapour collection control (including the recovery during filling of vehicle petrol tanks for installations that are "Stage II" vapour recovery system in place) (please attach) Year intervals as set out in section 21 of the Defra guide	
system	Schedule of examination and testing for vapour collection controls (in for vapour recovery during filling of vehicle petrol tanks for installation of the have a "Stage II" vapour recovery system in place) (please attach)	
equipm petrol t	Procedures or contingency measures in the event of vapour of nent failure (including the system for vapour recovery during the filling anks for instillations that are required to have a "stage II" vapour recover (Please attach)	of vehicle
be auto detecte of fuel deliver in acco section	ordance with section 5.20 of PG 1/14, faults of the vapour recovery somatically ed and indicated to the operator. The monitoring system will cut off on the faulty system if the fault is not rectified within the 168 hour (1 week) timordance with 15.25 of PG 1/14 the operator will: Identify the cause and take corre	the flow er period.

corrective action taken. The repairer will retest to demonstrate compliance. Operator will notify Regulator on completion.

B2.15 For petrol stations that are required to have a "stage II" vapour recovery system in place only, a certificate to confirm conformity with approval for use under the regulatory regimes of at least one European Union or European Free Trade Association country and to confirm that the hydrocarbon capture efficiency of the equipment is not less than 85% (i.e. that at least 85% of the displayed vapours are recovered, according to the relevant "type approval" test (see section 5.16 of this note), expressed as the ratio of the volume of hydrocarbon vapours displaced to the volume of petrol discharged (Please attach)

B2.16 For petrol stations that are required to have a "stage II " vapour recovery system in place only, details of testing of the vapour containment integrity in accordance with the manufactures specifications (to be undertaken prior to commissioning and periodically at least once every three years thereafter and always following substantial changes or significant events that lead to the removal and replacement of any of the components required to ensure the integrity of the containment system) (Please attach)

Not Applicable Monitored System LED display on Pump

B2.17 For petrol stations that are required to have a "stage II " vapour recovery system in place only, is an "automatic monitoring system" installed to automatically detect faults in the proper functioning of the petrol vapour recovery system including the automatic monitoring system; to indicate faults to the operator; and to automatically cut off the flow of fuel on the faulty delivery system if the fault is not rectified within 1 week.

	 _		١	
NO	\sum	YES	/	
	•			

B.3.1 Provide an **ass**essment of the potential significant local environmental effects of the foreseeable emissions (for example is there a history of complaints; is the installation in an air quality management area?)

No	complaints	received,	the stage	2 system	will imp	rove air	quality

Doc Reference:	
----------------	--

B.3.2 Are there any sites of special scientific interest (SSSIs) or European sites which are within 500metres of the installation

	YES, please give names of the sites
NO	Doc Reference
	Doc Reference

		· · · · · · · · · · · · · · · · · · ·
effect on such sites and if it is	to provide an asse	ation is likely to have a significant essment of the implications of the onservation (Natural Habitats etc)
Not Applicable		
Doc Reference:		
	(4 (8)	
B4 Environmental Statemen	ts ::	
		1 1
B4.1 Has an environmental imp Country Planning (Environmenta 1999/293, or for any other reason	I Impact Assessmer	n carried out under The Town and ht)(England & Wales) Regulations stallation?
NO	YES, (please supplimpact Doc Reference	ly a copy of the environment
	Doc Reference	
B5 Additional Information Please supply any additional information considering this application.		ald like us to take account of in
considering this application.	3 0 ·	
NO	At all	
Doc Reference	_0	r *
C1 Fees and Charges		
The enclosed charging scheme leady Your application cannot be process		
C1.1 Please state the amount en	nclosed as an applica	tion fee for this installation:
Cheques should be made payable	to:	

We will confirm receipt of this fee when we write to you acknowledging your application.

C1.2 Please give any company purchase order number or other reference you wish to be used in relation to this fee.

C2 Annual charges

If we grant you a permit, you will be required to pay an annual subsistence charge, failure to do so will result in revocation of your permit and you will not be able to operate your installation.

C2.1 Please provide details of the address you wish invoices to be sent to and details of someone we may contact about fees and charges within your finance section.

Shell Shared Service Centre	
PO Box 25071	
72 Gordon Street, London	
Postcode:G1 3WR	Telephone:

C3 Data Protection

The information you give will be used by the local authority to process your application. It will be placed on the relevant public register and used to monitor compliance with the permit conditions. We may also use and or disclose any of the information you give us in order to:

· consult with the public, public bodies and other organisations,

176 to 15

- carry out statistical analysis, research and development on environmental issues,
- provide public register information to enquirers,
- make sure you keep to the conditions of your permit and deal with any matters relating to your permit
- · investigate possible breaches of environmental law and take any resulting action,
- prevent breaches of environmental law,
- offer you documents or services relating to environmental matters,
- respond to requests for information under the Freedom of Information Act 2000 and the Environmental Information Regulations 2004 (if the Data Protection Act allows)
- assess customer service satisfaction and improve our service.

We may pass on the information to agents/ representatives who we ask to do any of these things on our behalf.

It is an offence under regulation 38 of the EP Regulations, for the purpose of obtaining a permit (for yourself or anyone else), to:

- make a false statement which you know to be false or misleading in a material particular,
- recklessly make a statement which is false or misleading in a material particular
- intentionally to make a false entry in any record required to be kept under any environmental permit condition
- with intent to deceive, to forge or use a document issued or required for any purpose under any environmental permit condition.

If you make a false statement

- we may prosecute you, and
- if you are convicted, you are liable to a fine or imprisonment (or both).

C4 Declaration

C4.1 Signature of current operator(s)*

I/We certify that the information in this application is correct. I/We apply for a permit in respect of the particulars described in this application (including supporting documentation) I/We have supplied.

Please note that each individual operator must sign the declaration themselves, even if an agent is acting on their behalf.

For the application from:

Installation name: SI	HELL WHITEHOUSE		
Signature	NS		
Name <u>Kerry Tor</u>	ns		
Position Retailer Cont	racting Assistant		
Date <u>17[™] FEBRUARY</u>	2009	· · · · · · · · · · · · · · · · · · ·	
	e di di parti		
Signature	F. A. B. 7 (1)	Add West	
Name			
Position		,	
Date			

^{*} Where more than one person is defined as the operator, all should sign. Where a company or other body corporate – an authorised person should sign and provide evidence of authority from the board of the company or body corporate.

4 K ZH - ZH

it. San A

¥į



GVR - FEF STAGE II VAPOUR RECOVERY COMPLIANCE CERTIFICATE

SHELL WHITEHOUSE

24-Jul-08

GVR - FEF Stage II Vapour Recovery Test Certificate

Completed certificate to be kept on site with site records and a copy retained by the contractor.

PART A	a. Work and Equipment Record	I
Date:	24/07/2008	8
Engineer	Name:	S.WALTON
Site Nam	e & Operator:	SHELL WHITEHOUSE
Address	of site:	665-667 NORWICH ROAD IPSWICH SUFFOLK IP1 6JZ
Dispense	r/Pump Make & Model:	Gilbarco SK700
Vapour R	ecovery system fitted:	Gilbarco VRC 700 & GR125
Vapour R	ecovery monitoring system fitted:	Gilbarco VMC
Tick all be	oxes that apply:	
	New Installation	
	New Pumps with Stage II	
✓	Stage II retrofit	
✓	Automatic monitoring retrofit	
	Work on Vapour Recovery System	
	Work on Automatic Monitoring System	1
V	Ordered by customer or other agency	
	Annual periodic test	
	3 yearly periodic test	
\checkmark	Test after modification or repair	
\checkmark		
Remarks:	LED TRAFFIC LIGHT EXPLAINED	O & UNDERSTOOD BY SITE MANAGER

SHELL WHITEHOUSE IPSWICH

GVR - FEF Stage II Vapour Recovery Test Certificate

PART B. VR Efficiency Test Record

The manufacturer's documentation, including approval certificate, contains data required for efficiency tests.

Correction factor for air (in manufacturer's documentation):

Maximum certified fuel flow rate:

42 L/min

Outdoor temperature:

26°C

Tolerance range for V/P ratio:

95%

to

105%

				V/P ratio at air test flow rate				
Pump side	Pump Number		Grade Name	rade Name Before ac	efore adjustment			
				[%]	[l/min]	[%]	[l/min]	
		G1	Unleaded	96	38			
1	2	G2	V Power Unl	96	38			
		G3						
		G1	Unleaded	96	38			
2	1	G2	V Power Unl	96	38			
		G3						
		G1	Unleaded	96	38			
1	4	G2	V Power Unl	97	38			
		G3						
		G1	Unleaded	96	38			
2	3	G2	V Power Unl	97	38			
		G3						
		G1	Unleaded	96	38			
1	6	G2	V Power Unl	96	38			
		G3					er adjustment (if licable)	
G1 Unleaded 97	38							
2	5	G2	V Power Unl	97	38			
_		G3	<u> </u>					
		G1						
1 1		G2				<u> </u>	 	
		G3						
		G1						
2		G2		\top				
		G3		 				

If more than 4 pumps see additional page 2A.

Note: If the Vapour Recovery monitoring device is equipped with a regulation or correction function then this has to be disabled during the measurements.

If an Automatic Monitoring system is fitted, is this operating correctly - indication for normal operation, alarm condition and stop condition. YES

Date of this inspection:

24/07/2008

Shell Whitehouse

Date next inspection due:

24/07/2011

Certifying Engineer:

S.WALTON

ADDITIONAL PUMPS

				V/	V/P ratio at air test flow rate				
Pump side	Pump Number		Grade Name	Before ad	Before adjustment		stment (if		
				[%]	[l/min]	[%]	[l/min]		
		G1							
1		G2							
		G3							
		G1							
2		G2							
		G3							
		G1							
1		G2							
		G3							
		G1							
2		G2							
		G3							
		G1							
1 1		G2							
		G3							
		G1							
2		G2			_				
		G3							
		G1							
1		G2							
		G3							
		G1							
2		G2							
		G3							

Note: If the Vapour Recovery monitoring device is equipped with a regulation or correction function then this has to be disabled during the measurements.

If an Automatic Monitoring system is fitted, is this operating correctly - indication for normal operation, alarm condition and stop condition. YES NO

Date of this inspection:

Date next inspection due:

Certifying Engineer:

SHELL WHITEHOUSE IPSWICH

GVR - FEF Stage II Vapour Recovery Test Certificate

PART C. Initial Installation Inspection and Test

Leak test executed and passed on Vapour Re	ecovery pipes & components:
X Inside of dispenser (retrofit kits)	Between dispenser and tank

	Test steps	Details - Pass/Fail or Values				
	rest steps	P1/2	P3/4	P5/6	P7/8	
1	Conforms with installation instructions.	PASS	PASS	PASS		
2	Visual inspection of Vapour Recovery system for security of fittings.	PASS	PASS	PASS		
3	Visual inspection of Vapour Recovery monitoring device - if fitted.	PASS	PASS	PASS		
4	Leak test to internal dispenser pipes and components. (Retrofit kits)	PASS	PASS	PASS	_	
5	Leak test to pipes connecting dispenser to tank or other external systems.	N/A	N/A	N/A		
6	Running of Vapour Recovery pump - no loose or vibrating pipes.	PASS	PASS	PASS		
7	Confirm operation of Vapour Recovery monitoring device and alarm test. Note 1	PASS	PASS	PASS		
8	Dry measurement at each petrol nozzle.	PASS	PASS	PASS		

Test steps		Details - Pass/Fail or Values			
		P9/10	P11/12	P13/14	P15/16
1	Conforms with installation instructions.				
2	Visual inspection of Vapour Recovery system for security of fittings.				
3	Visual inspection of Vapour Recovery monitoring device - if fitted.				
4	Leak test to internal dispenser pipes and components. (Retrofit kits)				
5	Leak test to pipes connecting dispenser to tank or other external systems.				
6	Running of Vapour Recovery pump - no loose or vibrating pipes.				
7	Confirm operation of Vapour Recovery monitoring device and alarm test. Note 1				
8	Dry measurement at each petrol nozzle.				

Note 1 The alarm signal and the switch off function has to be tested for every nozzle if the switch off function is nozzle specific.

Shell Whitehouse

Date of inspection: 24/07/2008

Certifying Engineer: S.WALTON



VAPOUR RECOVERY ALARM INDICATORS (TRAFFIC LIGHTS)

Your dispensers may be fitted with either one or two LED indicators ('Traffic Lights') on the display.

These are to indicate the status of the vapour recovery system and to alert you as to possible problems that may be about to occur, giving you time to arrange a service call.

The traffic lights will display one of three colours after a transaction (either green, amber or red).

THESE SHOULD BE CHECKED ON A DAILY BASIS!

The meaning of these is as follows:

Green - The vapour recovery system is OK and working within prescribed limits.

Amber - A series of consecutive transactions have fallen outside the vapour recovery tolerance.

The dispenser is now in alarm condition and will shut down in 7 days!

ARRANGE A SERVICE CALL AS SOON AS POSSIBLE!

Red - The fault has not been fixed within 7 days and the dispenser has therefore shut down!

The location of the LED indicators will vary depending on the type of dispenser. Details for each of the dispensers may be found on the following pages:

EUROLINE PAGE 2

ENTERPRISE PAGE 2


ENCORE 510 PAGE 3

EUROLINE GM PAGE 3

SK700 PAGE 4


EUROLINE:

If your dispensers are Eurolines, the traffic lights will be found on one side of the display head and will look as follows:




ENTERPRISE:

On the Enterprise, one LED will be found in the top left hand corner of each display bezel.




ENCORE 510:

On the Encore 510 there is an LED on each display bezel adjacent to the PPU (Price Per Unit) display/s.




EUROLINE GM:

On the Euroline GM, one LED can be found in the top left hand section of each dial face above the 'This Sale' window.



SK700:

On the SK700, one LED can be found in the top left hand section of each dial face, to the left of the 'Pence Per Litre' window.





Certificate Pursuant to section 12 of the Weights and Measures Act 1985

Certification No 2650/55

Valid Until 2 July 2016

In accordance with the provisions of section 12 of the Weights and Measures Act 1985, the Secretary of State for Trade and Industry hereby certifies as suitable for use for trade a pattern of a liquid flowmeter, as described in the descriptive annex to this Certificate, and having the following characteristics:-

DISPENSER:

Gilbarco SK700 as described in Certification

No 2650

KIOSK CONTROL UNITS AND POINT OF SALE SYSTEMS:

Any approved POS/KCU equipment previously

approved with Certification 2650

OUTDOOR PAYMENT

TERMINAL:

Any approved Outdoor Payment Terminal equipment

previously approved with Certification 2650

BANK NOTE ACCEPTOR:

Any approved Bank Note Acceptor equipment

previously approved with Certification 2650

VAPOUR RECOVERY SYSTEM:

With any of the Stage II Vapour Recovery Systems

fitted as described in the descriptive annex

Under the provisions of section 12(6) of the said Act, the validity of this certificate is limited as shown above.

Note: This certificate relates to the suitability of the equipment for use for trade only in respect of its metrological characteristics. It does not constitute or imply any guarantee as to the safety of the equipment in use for trade or otherwise.

Submitted by:

Gilbarco Veeder-Root Ltd

Crompton Close

Basildon Essex

SS 14 3BA

Signatory: R N Willans

Chief Executive

2 d. Million

National Weights & Measures Laboratory

Department of Trade and Industry

Stanton Avenue

Teddington

Middlesex TW11 0JZ United Kingdom

Date: 3 July 2006

Reference No: T1117/0016

CONTENTS

CERTIFICATION NO 2650/55

- 1 INTRODUCTION
- 2 CONSTRUCTION
- 3 OPERATION

ILLUSTRATIONS

Figure 1 Typical Vapour Recovery System

CERTIFICATION NO 2650/55

Descriptive Annex

1 INTRODUCTION

1.1 General

Stage II Vapour Recovery Systems are used during refuelling to recover the vapour contained within the vehicle fuel tank and are scheduled to become mandatory in the UK by 2010. They are normally required on Petrol grades only, and the recovered vapour is returned to the underground tank. Although the vapour recovery system is not itself a legal metrological requirement, NWML authorisation is required to permit the connection of the various systems described within this descriptive annex to the approved dispenser.

Stage II Vapour Recovery Systems have been in use in other European Countries, notably Germany. The Environmental (non weights and measures) approval of these systems in the UK will be based upon environmental approvals obtained in these other European countries. The systems described herein all have such approvals and are certified accordingly.

1.2 Vapour Recovery Monitoring

As well as the Vapour Recovery system, an optional Vapour Monitor system can be fitted. This checks for the correct operation of the system, and if after a number of consecutive transactions the system is found to be functioning incorrectly an Alarm system is activated. This indicates to the operator or owner of the Dispenser, that the Monitor has detected a fault condition with the Stage II Vapour Recovery System and the system should be serviced or repaired. The alarm can either be local at the Dispenser (Indicating Lamp) or can be remotely located in the kiosk area. If, after a certain period, the Dispenser has not been repaired, the appropriate fuelling position will be automatically disabled until the repair is carried out.

2 CONSTRUCTION

21 Components

The systems described typically consist of a mix of standard components described below:-

a) Vapour Recovery Nozzle Elafle:

Elaflex ZVA 200 GRV Series

Elaflex ZVA Slimline GRV Series

Alternatively any Vapour Recovery Nozzles

approved for use by TUV

b) Vapour Recovery Hose

Elaflex Conti Slimline 21 Series

Alternatively any Vapour Recovery Hoses

approved for use by TUV

c) Vapour Pumps

ASF 8014 Series

Durr MEX 0831 Series

Alternatively any Vapour Recovery Pumps

Stor Carly

gin ji

approved for use by TUV

(Note: These Vapour pumps are typically driven via either a single ended or double

-50004

ended AC Motor)

d) Proportional Valve Burkert 2832 series

Burkert 6022 series

e) Fuel / Vapour Splitter Adaptor Elaflex ZAF series

f) Electronic Control Unit for Burkert 1094 Series

Vapour Recovery System Gilbarco VRC390/392 Series

g) Optional Vapour Meter Gilbarco Veeder-Root GE1 Meter.

Alternatively any Gilbarco Veeder-Root Meter for Vapour Monitoring systems approved for

use by TUV

h) Electronic Control Unit Gilbarco VMC390/392 series

for Vapour MonitoringSystem Alternatively any Gilbarco Veeder-Root

Electronic Control Unit for Vapour Monitoring

systems approved for use by TUV

i) Kiosk Alarm Indicator Gilbarco KAI392

Any Kiosk Equipment (eg:POS) with suitable

Interface.

Alternatively any Gilbarco Veeder-Root

Electronic Control Unit for Vapour Monitoring

systems approved for use by TUV

22 Systems

221 Vapour Recovery Systems

The European Environmental approvals certificates for Vapour Recovery Systems normally specify the following components –

Nozzle type eg. Elaflex ZVA 200GR

Hose type eg: Elaflex Conti Slimline 21/8 Coax

Proportional valve

And Control Electronics eg: Burkert 6022 / 2832

Vapour Pump eg: Durr MEX 0831

They also specify the Maximum flowrate for each system, the maximum backpressure and the Correction Factor to be used when calibrating the system.

Any Vapour Recovery system using the components described in Section 2 can be used providing they have a suitable European environmental approval certificate (eg: TUV Certificate).

2.2.2 Vapour Monitor System

The European Environmental approvals certificates normally specify the following

Type Designation of the System

eg: Gilbarco VMC (Vapour Monitoring Controller)

Manufacturer

eg: Gilbarco GmbH & Co. KG Ferdinand-Henze-Str. 9 33154 Salzkotten

System Gas Flow Meter

eg: Gilbarco Veeder-Root GE1 Meter.

Any of the monitoring components described in Section 2 can be used providing they have an environmental approval certificate for such a Vapour Monitor System (eg: TUV Certificate) which lists the appropriate Monitoring component.

3 OPERATION

3.1 When fuelling commences, the fuel delivered displaces the vapour contained within the vehicle fuel tank and the vapour is therefore forced out. The vapour pump is used to collect the vapour as it emerges from the fuel tank. Referring to Figure 1, the path of the vapour flow is—

one il

Via the outer ring of the nozzle >
On into the inner core of the coaxial hose >
Into the splitter hose connector (ZAF) >
Out of the splitter hose connector into the vapour pipe >
Through the vapour monitor meter (if fitted) >
Through the proportional valve >
Through the Vapour Pump >

Then out through the shear valve and back to the underground tank

- 32 The Vapour Recovery Controller Electronics is used to match the recovered vapour rate with the fuel flow rate. It does this by adjusting the proportional valve to obtain the vapour flow rate in line with the fuel flow as indicated by the fuel meter pulser. This way, the vapour recovery volumetric efficiency is kept within the 95 to 105% level.
- 33 The Vapour Recovery Controller Electronics is calibrated using an external Gasmeter connected to a handheld terminal. The handheld terminal interfaces to the Vapour Recovery Electronics by a serial port and initiates a calibration sequence. This is accomplished without any fuel delivery and with only air being measured, also with a calibration factor being used which makes allowance for the difference between air and vapour and the particulars of the system components used.
- An optional Vapour Monitoring System may also be used. This is used to check the correct operation of the Vapour Recovery system. A Vapour meter is used to measure the vapour being recovered. This interfaces to the Vapour Monitor Electronics, which compares this with the fuel delivered and, if after a number of consecutive transactions the vapour recovered is outside of specification, the monitor will indicate an alarm. This gives the owner time to have the system repaired before the Fuelling point is automatically shut down.
- 3.5 If a Vapour Monitoring system is not used, the recovery system will need to be checked for correct operation on a regular basis.
- The Monitor Alarm can be either indicated at the Dispenser (eg: via an LED) or a signal can be sent to the Kiosk via the standard data communication line to the POS and indicated at the POS itself. Optionally, a special 'Kiosk Alarm Indicator' (KAI) can be fitted which interfaces to the Monitor system via a serial channel and indicates the alarm details in the kiosk.




Figure 1, Typical Vapour Recovery System (Non Vapour Recovery components shown within greyed area)





Zertifikat Nr. 85-2.156

Certificate No. 85-2.156

Die Prüfstelle für Gasrückführungssysteme der TÜV SÜD Industrie Service GmbH, Westendstr. 199, D-80686 München, bescheinigt die Prüfung gemäß dem Merkblatt:

"Systemprüfung für aktive Gasrückführungssysteme und deren Überwachungssysteme in Deutschland (Merkblatt I)" vom 17.6.2002

für folgendes Gasrückführungssystem: The TUV SUD Industrie Service GmbH Test Body for Vapor Recovery Systems, Westendstr, 199, D-80686 Munich, certifies having conducted tests as per the following code: "Testing of active vapour recovery systems and their monitoring devices in Germany (Code I)" of June 17, 2002 on the following vapor recovery system:

Zapfventil: Fuel-hose nozzlo. **ELAFLEX ZVA 200 GR**

Schlauch:

ELAFLEX Conti Slimline 21/8 Coax

Hose:

Steuerventil: Control valve:

Bürkert 6022 / 2832,

Ansteuerung Gilbarco VRC 390 und 390/2

Gilbarco control VRC 390 and 390/2

 Gasrückführungspumpe: Vapour recovery pump:

Gardner Denver Thomas 8014-5.0, 8014-6.0

Folgende Randbedingungen sind bei der Installation einzuhalten: The following general conditions must be observed during installation:

maximaler Kraftstoffvolumenstrom:

42 I/min

Maximum volumetric fuel-flow rate: maximaler Gegendruck in der Rückführleitung:

mbar 75

Maximum counter pressure in recovery line.

Korrekturfaktor für die Systemeinstellung mit Luft bei simuliertem Kraftstoffvolumenstrom von 38 l/min:

1.08

Correction coefficient for system settings with air by simulation of a volumetric fuel-flow rate of 38 l/min.

Der geforderte Wirkungsgrad von mindestens 85 % wurde nachgewiesen.

Contract Songe of

The required minimum efficiency ratio of 85% was proved.

Das Gasrückführungssystem entspricht dem Stand der Technik im Sinne der 21 BlmSchV (Verordnung zur Begrenzung der Kohlenwasserstoffemissionen bei der Betankung von Kraftfahrzeugen) vom 07.10.1992 zuletzt geandert am 6.5.2002

The vapour recovery system corresponds to the state of the art as defined in the 21st BimSchV (Airpollution Control Regulation on the restriction of hydrocarbon emissions during vehicle refueling) of October 7, 1992, last amended on May 6, 2002.

München, 11.09.2007 Munich, 11 September 2007

Der Sachverständige The officially authorized expert

Folker

Peter Szalata

On-Site Sign-off Document



4

All Clearance Certificates and associated H&S documents completed [
Work completed using correct H&S procedures at all times						
All Dispensers retrofitted with Stage II VR components						
All equipment tested and certified						
Appropriate PPE wor	n at all times					
Site left operational a	and fully Stage II VR	compliant				
Date: _			_			
Signed (Lead Engineer)						
Signed (Site Manager)		= 8	_			
	rother of	1 K 16.7(4.)				

Shell white is Norwick Xd

Part B Application form

Application to vary a permit for a Part B service station to add PVR Stage II

Local Authority Pollution Prevention and Control
Pollution Prevention and Control Act, 1999
Environmental Permitting (England and Wales) Regulations 2007

Introduction

When to use this form

Use this form if you are applying for a variation to an existing service station permit in order to extend it to cover the operation of PVR Stage II.

A fee is only required to be enclosed if the variation involves a 'substantial change'. A substantial change is defined as "a change in operation which, in the opinion of the competent authority [the regulator] may have significant <u>negative</u> effects on human beings or the environment". (Closure of an existing service station and the building of a new replacement station at another location is likely to require a full fresh application, ie not constitute a variation.)

When complete, send the form and the fee and any additional information to:

Insert local authority address

If you need help and advice

We have made the application form as straightforward as possible, but please get in touch with us at the local authority address given above if you need any advice on how to set out the information we need.

	_APPC applica	tion form: to be compl	eted by the operator	
For Local A	uthority use			
Application	reference	Officer reference	Date received	
A4 4 Nome	of the manifest			
Shell White	of the premise	S		
		aa af tha mramiaaa		
		ss of the premises		
Postcode:	wich Road, lps	•	472 220050	
FUSICUAE.	IF I OJZ	Telephone: 01	413 2303 30	
A1.3. Refere	ence number of	existing PVR Stage I per	rmit for the installation	
LAPPC PER	MIT REG NO 1	.2/RJD/13		
A2.1. The applicant - Please provide the full name of company or corporate body or the name of the sole trader or the names of the partners				
SHELL UK I	_IMITED			
Trading/busi	ness name (if d	ifferent)		
	• • • • • • • • • • • • • • • • • • • •			
Registered C	Office address			
Shell Centre York Road, London	,			
Postcode: S	E1 7NA Telep	hone: 0207 934 1234		
A2.2. Holdin	g companies			
	or a subsidiary anies Act 2006?		thin the meaning of section 1159	
□ No				

X

Yes

If yes? Name of ultimate holding company: SHELL TRANSPORT AND TRADING COMPANY PLC

Ultimate holding company registered office address

SHELL CENTRE YORK ROAD LONDON

Postcode: .SE1 7NA Telephone: 0207 934 1234

A3 Who can we contact about your application?

It will help to have someone who we can contact directly with any questions about your application. The person you name should have the authority to act on behalf of the operator - This can be an agent or consultant.

the operator - This can be an agent or consultant.						
Name: Kerry Toms						
Position: Retailer Contracting Assistant						
Address:						
P O Box 403 Staines Middlesex						
Postcode: TW18 3ZB Telephone: 0845 309 3091						
Fax number: 01784 897 845 email address: kerry.toms@shell.com						
B. About the installation						
B1.1 Is PVR Stage II equipment already fitted:						
No No						
X Yes						
B1.2 If the answer to B1.1 is "no",						
a) when do you intend to fit it						
b) what arrangements are in place (eg contract with installers) to fit it						

B2.1 What systems have been installed or is it intended to install to comply with PVR Stage II?

See Attached
Doc Reference See attached
B2.2 What is or will be the vapour/petrol ratio?
See Attached
B2.3 Please attach process diagrams and plans of VPR Stage II system, including pipework layout.
Doc Reference: See Attached
B2.4 What arrangements will be/have been made for preventative maintenance of the PVR Stage II equipment.
Doc Reference: See Attached
B2.5 What arrangements will be/have been made to ensure relevant staff are adequately familiar with and trained in the use of the PVR Stage II equipment.
Doc Reference: See Attached
B2.6 Please attach procedures and contingency measures in the event of vapour containment equipment failure (including the system for vapour recovery during filling of vehicle petrol tanks).

B2.7 Please provide a certificate to confirm conformity of the PVR Stage II equipment with approval for use under the regulatory regimes of at least one European Union or European Free Trade Association country and to confirm that the

Doc Reference: See Attached

hydrocarbon capture efficiency of the equipment is not less than 85% (ie that at least 85% of the displaced vapours are recovered, according to the relevant 'type approval' test (see Section 5.16 of PG1/14(06)), expressed as the ratio of the volume of hydrocarbon vapours displaced to the volume of petrol discharged.

Doc Reference: See Attached

B2.8 What arrangements will be put in place to test delivery systems and vapour recovery systems, including the testing of the vapour/petrol ratio? Please provide details of testing of the vapour containment integrity in accordance with the manufacturer's specifications (to be undertaken prior to commissioning and periodically at least once every 3 years thereafter and always following substantial changes or significant events that lead to the removal or replacement of any of the components required to ensure the integrity of the containment system).

Doc Reference: See Attached

DOC K	elefence. See Attached
autom systen and to	Is an "automatic monitoring system" installed, or will it be installed, to atically detect faults in the proper functioning of the petrol vapour recovery including the automatic monitoring system; to indicate faults to the operator automatically cut off the flow of fuel on the faulty delivery system if the fault is stifled within 1 week?
	No
X	Yes
В3	Additional Information
	supply any additional information, which you would like us to take account of sidering this application.
Doc Re	eference: See Attached

C1. Fees and Charges

C1.1. Please enclose the relevant sum if this variation involves a substantial change, and state the amount enclosed.

\sim											
*											

Cheques should be made payable to:

We will confirm receipt of this fee when we write to you acknowledging your application.

C1.2. Please give any company purchase order number or other reference you wish to be used in relation to this fee.

C2. Annual charges

If we grant you a permit, you will be required to pay an annual subsistence charge. If you don't pay, your permit can be revoked and you will not be able to operate your installation.

C2.1.If different to details provided in relation to your current PVR Stage I permit, please provide details of the address you wish invoices to be sent to and details of someone we may contact about fees and charges.

Shell Shared Service Centre Glasgow Ltd P O Box 25071 72 Gordon Street Glasgow

Postcode G1 3WR

Telephone.

C3. Commercial confidentiality

C3.1. Is there any information in the application that you wish to justify being kept from the public register on the grounds of commercial or industrial confidentiality?

If Yes, please provide full justification, considering the definition of commercial confidentiality within the EP Regulations (See the General Guidance Manual).

C4. Data Protection

The information you give will be used by the Local Authority to process your application. It will be placed on the relevant public register and used to monitor compliance with the permit conditions. We may also use and or disclose any of the information you give us in order to:

- consult with the public, public bodies and other organisations,
- carry out statistical analysis, research and development on environmental issues.
- provide public register information to enquirers,
- make sure you keep to the conditions of your permit and deal with any matters relating to your permit
- investigate possible breaches of environmental law and take any resulting action.
- prevent breaches of environmental law,
- offer you documents or services relating to environmental matters,
- respond to requests for information under the Freedom of Information Act 2000 and the Environmental Information Regulations 2004 (if the Data Protection Act allows)
- · assess customer service satisfaction and improve our service.

We may pass on the information to agents/ representatives who we ask to do any of these things on our behalf.

It is an offence under regulation 38 of the EP Regulations, for the purpose of obtaining a permit (for yourself or anyone else) to:

- make a false statement which you know to be false or misleading in a material particular,
- recklessly make a statement which is false or misleading in a material particular.

If you make a false statement

- we may prosecute you, and
- if you are convicted, you are liable to a fine or imprisonment (or both).

C5 Declaration: previous offences (dele	ete whichever is inapplicable)
---	--------------------------------

I/ certify

EITHER

No offences have been committed in the previous five years which are relevant to my/our competence to operate this installation in accordance with the EP Regulations.

OR

The following offences have been committed in the previous five years which may be relevant to my/our competence to operating this installation in accordance with the Regulations:
Troguestorio.
Signature ()

Name: Kerry Toms

Position: Retailer Contracting Assistant

Date: 7TH July 2009

6 Declaration

C6.1 Signature of current operator(s)*

I/We certify that the information in this application is correct. I/We apply for a permit in respect of the particulars described in this application (including supporting documentation) I/We have supplied.

Please note that each individual operator must sign the declaration themselves, even if an agent is acting on their behalf.

For the application from:
Premises name: Shell Whitehouse
Signature COCOCO
Name: Kerry Toms
Position: Retailer Contracting Assistant
Date: 7 th July 2009
Signature
Name
Position
Date

^{*} Where more than one person is defined as the operator, all should sign. Where a company or other body corporate – an authorised person should sign and provide evidence of authority from the board of the company or body corporate.

VAPOUR RECOVERY - STAGE 1B-Emergency Action Plan

All service stations have now been fitted with a vapour recovery system known as Stage 1B.

Stage 1B prevents vapours being discharged into the atmosphere during a tanker delivery by routing the vapours back to the tanker where they are collected and taken back to the terminal.

This process requires a permit (Similar to your Petroleum Licence).

Part of the permit requirement is that you have an <u>emergency action plan</u> in place should a leak occur in the vapour recovery system during a delivery. Whilst this situation is unlikely to be dangerous, it may cause some nuisance to your neighbours, therefore please carry out the following actions.

- 1. Ensure the driver stops the delivery.
- 2. Inform Retailer Maintenance Support on **0800 731 5555** so that the correct contractor can be sent to site to fix the problem.
- 3. Contact the Retailer Call Centre on 0800 731 5555 to record the incident.
- 4. Cancel further deliveries until the leak has been fixed.
- 5. Inform your local Environmental Protection Officer, name and telephone number should be on the permit.
- 6. Record the incident in your log sheet Incidents of vapour leak or vapour lock.

If you have any questions about this procedure please contact the HSSE Manager - don't wait until you have a problem.

- 1

VAPOUR RECOVERY - STAGE 2-Operation and Records

197

All service stations are now being fitted with a vapour recovery system known as Stage 2.

Stage 2 prevents vapours being discharged into the atmosphere during the filling of the vehicle fuel tank by routing the vapours back to the underground tank from where they are transferred to the tanker during a fuel delivery and taken back to the terminal.

This process requires a Permit (Similar to your Petroleum Licence).

STATE OF THE

The vapour recovery system has the benefit of automatic monitoring. Each pump has a LED display that should be checked on a daily basis.

- 1. In normal operation the LED is GREEN
- 2. In the event that insufficient vapour is being collect by the vapour recovery system the LED will change to orange, and an alert will be printed on the end of day and end of shift reports
- 3. Contact the Retailer Call Centre on **0800 731 5555** to report the incident and request that the contractor attend the site to resolve the issue.
- 4. If the fault is not fixed within 7 days the pump will automatically stop operating and no more fuel can be dispensed from that pump until a contractor has attended and fixed the problem.
- 5. Record the incident in your log sheet Incidents of vapour leak or vapour lock.

If you have any questions about this procedure please contact the HSSE Manager - don't wait until you have a problem.

The Retailer should ensure that at all times the following are available for inspection:-

- 1. A copy of the permit
- 2. The log book
- 3. Staff training records
- 4. Plan of the site and site pipe work
- 5. Copy of the compliance/ testing certificate

VAPOUR RECOVERY – Staff Training

All staff should be trained on the operation of the vapour Recovery system and provided with refresher training once every 12 months.

Training should include the following items:-

- a. Basic principles of vapour balancing related to the type of VR System.
- b. The safety precautions to be followed before, during and after a delivery to ensure that the system functions correctly so there is no spillage of petrol should there be an equipment failure.
- c. Their statutory obligations not to permit the delivery to commence until the vapour balance hose has been properly connected by the driver.
- d. The reasons for and the correct sequence in which the vapour balance hose should be connected.
- e. The signs and symptoms of vapour leaks.
- f. Monitoring the delivery for vapour leaks and the reporting/recording procedure of instances of vapour lock, vapour leak, equipment failures, or unusually slow deliveries.
- g. The precautions to be taken should there be a malfunction of the equipment which over-pressurises the system.

Pollution Prevention and Control Act 1999 Environmental Permitting (England and Wales) Regulations 2007 VAPOUR RECOVERY TRAINING

It is a requirement of your 'Permit' that anyone who's duties include using, or supervising the use of, and maintaining the vapour recovery system must be trained in the use of the vapour recovery system and be informed of the Permit Holder's responsibilities and their individual roles and responsibilities in achieving them.

It is therefore important that anyone who is a designated 'Competent Person' for the receipt of fuel deliveries is trained in:

- The Permit Holder's responsibilities and their individual roles and responsibilities in achieving them.
 (See site Permit Conditions)
- 2. The correct procedure for connection of vapour recovery hose.
- 3. Action required as a result of a leak in the vapour recovery system during a delivery. (See attached Emergency Action Plan)

Please ensure that relevant staff members have been trained in the above, been signed off as having been trained, and the sign off below filed with Competent Person Training records.

Staff Member	Permit Responsibilities	Vapour Recovery Hose Connection	Emergency Action Plan	Trainer Signature	Trainee Signature	Date
<u></u>						
			V 1			
	1 (A) (B) (A) (A) (A) (A) (A) (A) (A) (A) (A) (A		1 1 1			-
		:	: .			,
			1.51			

SPECIMEN APPLICATION FOR AUTHORISATION

The following is a specimen application form which has been the subject of consultation with industry representatives and members of the former IPLA (Her Majesty's Inspectorate of Pollution/Local Authority Enforcement Liaison) Committee. Given the consistent nature of service station operations, it is likely to be more efficient for both industry and local enforcing authorities to make use of this form in all cases.

In accordance with the Environmental Protection (Prescribed Processes & Substances Etc) (Amendment) (Petrol Vapour Recovery) Regulations 1995, SI 2678, applications may not be made more than 15 months before the date on which authorisation is required. (See Clause 9). Operators are strongly advised to submit their applications no later than 9 months before the relevant date in order to allow local authorities sufficient time to determine the application. Operation without an authorisation after the relevant date would be an offence.

References to the term "process" are references to the unloading into storage of petrol. The operator of the process under the terms of the Act is most likely to be the person with management responsibility for the procedures on site. This does not, however, absolve other people of their responsibilities (for instance of drivers in the case of following unloading procedures or of the equipment owners in the case of installation of equipment) since action can be taken directly under section 158 of the Act.

Further advice on transfer of authorisations and on process changes may be found in General Guidance Note GG1—"Introduction to Part I of the Act"; ISBN 0 11 752423 9, published by HMSO, £5 net.

Application for Authorisation; Part I, Environmental Protection Act, 1990

Section A: General Information

1. Name and address of premises where process is/will be carried out

SHELL WHITE HOUSE (675) 665, MORGICH ROAD

TOSSICH SUFFOCK POST Code IP 1 67Z

Telephone No 01473 Contact Name ZARA BEHBEHANI

ROSTO

Position CURRENT SITE

MANAGER.

2. Name and address of appli		SHELL U.K. LIMITED MERCURY HOUSE HANGER GREEN
*****************	200200000000000	

Telephone NoO/8/758- Cont	act Name	TAMES FLYNN
Telephone NoC! 81 758- Cont	Position Loc	AL AUTHORITY
3. Name and address of regist case of partnerships, names and homes.	ne addresses o HELL UK LTI	f the partners. O.
	HE STRAND	
Telephone No 0171 257-Cont		
.3000	Position	N/A
4. Name of the ultimate holding	g company (if applicable)
G REPORTATION OF THE PARTY.	M. /.A	* * * * * * * * * * * * * * * * * * * *
9 C. F. B. F. F. C. F.	· ·	
5. Address for correspondence	if different	from (1) above
	SHELL U.K. I	
	HANGER GR	
	EALING LONDON W5	3BA
6. Enclose a map/plan with location where the process is/process is/will be carried out please indicate the exact location	will be car: on only p	ried out. Where the art of the prem ise s
		5
7. Is the service station loc quarters or working areas? See	Clause 9	r permanent living
8. When was vapour balancin will it be installed?		at installed or when
TICTALLED RS	· • · · · ·	1000 /1000

Section B. Process and Control Information

9. Volume of petrol unloaded into the service station in each of the last three calendar years (see Clause 9 of this Note for the relevant timescales); in cubic metres (ie litres divided by 1000). Circle the appropriate band

YEAR	VOLUME OF PETROL/m ³								
1997	<100	100-500	501-1000	(1000)					
teab	<100	100–500	501-1000	1000					
११९५	⁻ <100	100–500	501-1000	(1000)					

10. Are deliveries "Driver Controlled"



11. At a maximum, how many tanker compartments discharge into storage tanks at any one time, or will do so once a vapour balancing system is in place. If the latter information is not known, a statement of what assessment will be made to determine this information and within what timescale. The information supplied under item 11 should be supplemented by a site specific assessment. (See Clause 17).

40 TO THREE (03)

12. Measures taken or to be taken for vapour emission control, both during unloading and in storage

TANK VENTING SYSTEM HAS MANIFOLD STAGE IB VAPOUR BALANCING SYSTEM INSTALLED.

13. Please attach process diagrams and plans of vapour balancing equipment (including height and location of tank vent pipes)

SEE ATTACHED PLAN

14. Unloading procedure and instructions (please attach)

SEE ATTACHED PACK

Operating Staff [Details should be specific to on-site staff and include general statements concerning delivery drivers]
SEE ATTACHED PACK
16. Schedule of maintenance of vapour balancing controls [please attach]
SEE ATTACHED PACK
17. Schedule of examination and testing for vapour balancing controls [please attach]
SEE ATTACHED Pack,
18. Procedures or contingency measures in the event of vapour containment equipment failure. [please attach]
SEE ATTACHED PACK.
You may also supply any other information you wish the Local Authority to take into account when considering your application.
I hereby certify that I am authorised to sign to sign this application and all the information contained in this application is correct to the best of my knowledge and belief.
Name (BLOCK CAPITALS): JAMES FLYNN
Signature: Janes Bate: FRI 16TH Oct 9
Designation: LOCAL AUTHORITY LIAISON IPSWICH
Fee attached (cheques payable to the BOROUGH Council) C 100-00